Metal Shear LXT®

DJS161Z

18V • 4 300 min^{-1}

A high capacity metal shear with a radius of 250 mm

A cordless metal shear for straight and curved cuts with a radius of 250 mm, cuts a clean-edged strip from the middle. Cutting capacity of 2.5 mm for aluminium and 1.6 mm for steel. The tool has a stroke rate of 4 300 min^{-1} and it is equipped with a battery protection system. Tool only, battery and charger not included.



LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	4300 min^{-1}
Min. Internal Cutting Radius	250 mm
Cutting Capacity Aluminium (Up To 200N/Mm^2)	2,5 mm
Cutting Capacity Mild Steel (up to 400N/mm^2)	1,6 mm
Cutting Capacity Stainless Steel (up to 600N/mm^2)	1,2 mm
Vibration Level, Cutting Sheet Metal	13,0 m/s^2
Sound Pressure Level (L_{pA})	71 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Uncertainty (K Factor), Cutting Sheet Metal	1,5 m/s^2
Tool weight with battery	1,8 - 2,2 kg

User benefits

- Compact and lightweight design
- The material to be cut is removed in the middle as a strip; the material around the edges remains intact.
- Electronic overload protection protects the user and the device
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381672078

Link to product - www.makitauk.com

Related products

Standard AC

783201-2
Hex Wrench 3Mm



Optional AC

762013-6
Thickness Gauge 0,5 / 1,0 / 1,5 mm



783201-2
Hex Wrench 3Mm



792533-6
Side Blade Set 1,6 mm



792534-4
Centre blade 1,6 mm



792537-8
Centre blade 1,0 mm

821550-0
Makpac case (2)



837636-0
MakPac (2) Inlay



Other

User manual

Parts drawing