Rotary Hammer LXT®

DHR242RTJW

18V • SDS-PLUS • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer with dust extraction

An efficient rotary hammer for SDS-PLUS bits with an anti-vibration handle and dust extraction. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min^{-1}. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Two 5.0Ah batteries and a rapid charger in a Makpac case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min^{-1}
Impacts per Minute (IPM)	0 - 4700 min^{-1}
Max. Drilling Diameter in Concrete	24 mm
Optimum Drilling Diameter Range in Concrete	4 - 16 mm
Drilling diameter with TCT core bit	54 mm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	27 mm
Impact Energy	2,0 J
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L_{WA})	99 dB(A)

User benefits

- Brushless maintenance-free and long-life motor
- Low power consumption thanks to brushless motor
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381876094

Link to product - www.makitauk.com

Related products

Standard AC

821552-6
Makpac case (4)



199563-2
Dust Extraction System DX06



324219-0
Depth Gauge

424474-5 (5x)
Sealing Cap



450128-8
Battery cover, LXT®, 14,4 – 18V



Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



DC18RC
Battery Charger LXT®



Optional AC

821552-6
Makpac case (4)



D-16368
Chisel set SDS-PLUS, 5 pcs



199557-7
Replacement Hepa filter



196165-5
HEPA filter



424474-5
Sealing Cap



835A31-4
MakPac Type 4 Inlay



Other

User manual

Parts drawing