Die Grinder

GD0602

400 W • 25 000 min^{-1} • 6 mm

Compact tool with safety switch underneath

A slimline, light die grinder with a 6 mm collet and paddle switch. Suitable for small-scale grinding, including burr removal. Achieves a high speed: 25 000 min^{-1}.



Technical specifications

Continuous Input Power 240V	400 W
No load speed	25000 min^{-1}
Collet Capacity	6 mm
Wheel point max.	38 mm
Collar Clamping Diameter	43 mm
Power Supply Cord	2,5 m
Sound Pressure Level (L_{pA})	75 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Weight Without Cable	1,4 kg
Product Dimensions (L x W x H):	264 x 82 x 82 mm
Vibration Level, Surface Grinding	2,5 m/s^2
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s^2

User benefits

- Vent slots designed to direct exhaust air away from the user
- Slim body design for a good grip
- Protective zig-zag varnish seals the armature from dust and debris for longer tool life
- Slide switch with lock-on for continuous use

EAN 0088381097109

Link to product - www.makitauk.com

Related products

Optional AC

193144-4
Collet Cone 1/8" Set with Nut



763669-8
Collet cone 3 mm



763670-3
Collet cone 6 mm



763673-7
Collet Cone 6,35 mm



B-52716
TCT Burr 10 x 20 x 6 mm, Standard

B-52722
TCT Burr 10 x 20 x 6 mm, Diamond

B-52738
TCT Burr 10 x 20 x 6 mm, Non-

B-52744
TCT Burr 10 x 20 x 6 mm, Standard

B-52750
TCT Burr 10 x 20 x 6 mm, Diamond

B-52766
TCT Burr 10 x 20 x 6 mm, Non-

Other

User manual

Parts drawing