BROUGHTON PLANT HIRE

HIRE | SALES | SERVICE
Specialists for over 40 years

MAKITA Plunge Saw

The Makita SP6000 Plunge Saw is designed for precise, clean and accurate cutting, making it ideal for materials such as timber, worktops, flooring and decking. It can be used with a guide rail for straight, controlled cuts and allows for easy depth adjustment and close-to-wall cutting. The plunge action also makes it useful for starting cuts in the middle of a workpiece, rather than only from an edge.

SPECIFICATIONS

- Continuous Input Power: 1300W
- No Load Speed: 2200–6400 min^{-1}
- Max Cutting Depth at 90°: 56mm
- Max Cutting Depth at 48°: 38mm
- Max Cutting Depth at 45°: 40mm
- Blade Diameter: 165mm
- Bore Size (Arbor Diameter): 30/30mm
- Power Supply Cord: 4.0m
- Sound Power Level (LWA): 103 dB(A)
- Sound Pressure Level (LpA): 95 dB(A)
- Noise Uncertainty (K Factor): 3 dB(A)
- Weight Without Cable: 4.1kg
- Product Dimensions (L × W × H): 341 × 225 × 250mm
- Max Bevel Range (Right): -1–48°
- Vibration Level, Cutting Wood: ≤ 2.5 m/s^2
- Vibration Uncertainty (K Factor), Cutting Wood: 1.5 m/s^2
- Vibration Level, Cutting Metal: ≤ 2.5 m/s^2
- Vibration Uncertainty (K Factor), Cutting Metal: 1.5 m/s^2
- Vacuum Cleaner Connection Ø in/out: 35/43mm

FEATURES

- Compatible with guide rail for more precise cuts
- Close-to-wall cutting; only 18 mm away from wall
- Precision accurate cutting delivers a splinter free mirror finish
- Electronic speed control maintains constant speed under load for smoother, higher quality cutting
- Easy to set depth adjustment with large scale
- Soft start minimises start-up shock and makes the tool start smoothly
- Ergonomic rubberised front grip and handle provide added comfort

