# 110 V Plunge Cut Saw

# SP6000J/1

1 300 W • 2 000 – 5 800 $min^{-1}$ • 165 mm

**Precise plunge cut circular saw**

A precise plunge cut circular saw for accurate cutting. Ideal for installing furnishing or decking. Recommended for use with a guide rail. A motor capacity of 1 300 W and cutting capacity of 56mm. Speed can be adjusted between 2 000 – 5 800 $min^{-1}$. Comes in a Makpac case.

## Technical specifications

| | |
|---|---|
| Continuous Input Power | 1300 W |
| No load speed | 2200 - 6400 $min^{-1}$ |
| Max. Cutting Depth at 90° | 56 mm |
| Max. Cutting Depth at 45° | 40 mm |
| Max. Cutting Depth at 48° | 38 mm |
| Max. Bevel Range (Right) | -1 - 48 ° |
| Blade Diameter | 165 mm |
| Bore Size (Arbor Diameter) | 20 / 30 mm |
| Mechanical brake | ✓ |
| Sound Power Level ($L_{WA}$) | 103 dB(A) |
| Sound Pressure Level ($L_{pA}$) | 95 dB(A) |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vibration Level, Cutting Wood | ≤ 2,5 $m/s^2$ |
| Weight Without Cable | 4,1 kg |
| Vibration Uncertainty (K Factor), Cutting Wood | 1,5 $m/s^2$ |

## User benefits

- Compatible with guide rail for more precise cuts
- Close-to-wall cutting; only 18 mm away from wall
- Precision accurate cutting delivers a splinter free mirror finish
- Electronic speed control maintains constant speed under load for smoother, higher quality cutting
- Easy to set depth adjustment with large scale
- Soft start minimises start-up shock and makes the tool start smoothly
- Ergonomic rubberised front grip and handle provide added comfort

## EAN 0088381639002

**Link to product - www.makitauk.com**

# Related products

## Standard AC

**687329-7**
Band

**726087-1**
Carbide Tipped Saw Blade 165

**783203-8**
Hex Wrench 5 Mm



**821552-6**
Makpac case (4)



**838390-9**
Inner tray (4)



## Other

**User manual**

**Parts drawing**