
UTS SALES AND REPAIRS


A SAFER WAY TO REACH NEW HEIGHTS

Double Width Tower	Working Height	Platform Height
2.5m Long x 1.45m Wide	9.2m	7.2m



Tower Components

Item	Description	Quantity
1	150mm Locking Caster	4
2	Adjustable Leg 500mm	4
3	1m 4 Rung Frame	0
4	1.5m 6 Rung Frame	0
5	2m 8 Rung Frame	8
6	2.5m Trapdoor Platform	4
7	2.5m Fixed Platform	1
8	2.5m Horizontal Brace	18
9	2.7m Diagonal Brace	13
10	S1 Stabiliser	4
11	S2 Stabiliser	0
12	Toeboard Clips	4
13	Double End	2
14	2.5m Side	2



*Folding single piece Aluminum toeboard available as an upgrade

Technical information:

Base Dimensions:	(L)2.5m X (W)1.45m
Maximum Platform Height (ph):	7.2m
Maximum Working Height (wh):	9.2m
Maximum Working Load Per Platform:	275kg
Maximum Working Load Per Tower: (including tower weight)	950kg
Weight:	254.6kg

01227 860085
Mon-Fri, 8am until 5pm

For More Information:
info@towersandpodiums.co.uk
We reply within 1 hour
Mon-Fri, 8am until 5pm

T&RGETMARK CERTIFIED
BS EN 1004-1:2020
BS EN 1004-2:2021
TM1008
testandresearch.org

MADE IN BRITAIN

FORS FLEET OPERATOR RECOGNITION SCHEME