BROUGHTON PLANT HIRE

HIRE | SALES | SERVICE
Specialists for over 40 years

3T Aluminium Gantry 2.2-3.6m

The Easy-Rig Aluminium Gantry is a lightweight, portable and fully customisable lifting solution, ideal for use in confined spaces, rooftops, lift shafts and other challenging environments. It features two A-frames with lockable 360° castors, a 3m interchangeable beam and external trolley, and can be used with a range of manual or powered lifting equipment.

SPECIFICATIONS

- Safe Working Load (SWL): 3,000 kg
- Support Height: 2,200–3,600 mm
- Support Height Increment: 200 mm
- Beam Length: 3 m
- Working Span: 1,770 mm
- Bottom Span: 2,496 mm
- Total Gantry Weight: 144.5 kg
- Certification: Fully certified and tested



FEATURES

- Lightweight aluminium construction for easy transport
- Portable, fully customisable gantry design
- Ideal for lifting in confined spaces, silos, rooftops, lift shafts and water treatment works
- Two A-frames and a 3m beam
- 160mm diameter castors with 360° rotation and brakes
- External trolley supplied for lifting applications
- Hitch supplied for raising the support
- Interchangeable beams allow different beam lengths to be used
- Compatible with manual chain blocks, lever hoists, electric hoists and the RUP502-T lifting winch
- Suitable for use in clean environments and a wide range of workplaces