BROUGHTON PLANT HIRE

HIRE | SALES | SERVICE
Specialists for over 40 years

FESTOOL Dry Wall Planer

The Festool LHS 2 225 EQI-Plus 110V is a long-reach sander designed for smooth, efficient sanding of walls and ceilings. Its LED light ring highlights surface imperfections, while adjustable suction reduces user fatigue.

SPECIFICATIONS

- Power Consumption: 400 W
- Eccentric Motion Speed: 5,000–8,500 min^{-1}
- Sanding Stroke: 4 mm
- Replaceable Sanding Disc Diameter: 220 mm
- Sanding Material Diameter: 225 mm
- Length: 1.2 / 1.65 m
- Dust Extraction Connection Diameter: 36 / 27 mm
- Cable Length: 4 m
- Product Weight (Without Accessories): 5 kg
- Transport Weight (Including Accessories): 11.3 kg
- Drive Type: Mains
- Total Vibration Average (Ah): 2.5 m/s^2
- Noise Uncertainty (K): 3 dB
- Vibration Uncertainty (K): 1.5 m/s^2
- A-Weighted Sound Power Level (LWA): 81 dB(A)
- A-Weighted Sound Pressure Level (LpA): 73 dB(A)

FEATURES

- LED Light Ring – Highlights surface unevenness during sanding to reduce the need for reworking.
- Eccentric Sanding Motion – Produces smooth, high-quality surfaces without grooves.
- Adjustable Suction Power – Helps the sander support its own weight against walls and ceilings, reducing strain on the arms and back.
- Reduced User Fatigue – Makes extended sanding work more comfortable with less physical effort.