BROUGHTON PLANT HIRE

HIRE | SALES | SERVICE
Specialists for over 40 years

HILTI TE60 ATC Drill

The Hilti TE 60 is a powerful combihammer designed for hammer drilling and chiseling in concrete and masonry, with additional drilling capabilities in metal and wood. Its ATC and AVR systems provide improved control and reduced vibration, while the versatile operating modes make it suitable for a range of demanding construction and renovation applications.

SPECIFICATIONS

- Rated power: 1,300 W
- Rated voltage: 110 V / 230 V
- Rated current: 14.8 A at 110 V / 6.9 A at 230 V
- Mains frequency: 50–60 Hz
- Weight: 6.4 kg
- Dimensions: 480 x 115 x 274 mm
- Hammer drilling speed: 350/min
- Single impact energy: 7.3 J
- Single impact energy, half power: 3.6 J
- Chuck: TE-Y
- Protection class: Class II (double insulated)
- Sound power level: 107 dB(A)
- Sound pressure level: 96 dB(A)
- Sound level uncertainty: 3 dB(A)

FEATURES

- SDS Max (TE-Y) quick-change chuck
- Active Torque Control (ATC) for improved user safety and control
- Active Vibration Reduction (AVR) system
- Variable speed control for smooth hole starting and chiseling
- 3-mode function selector: hammer drilling, chiseling and chisel adjustment
- Full or 50% power selection
- Vibration-absorbing side handle and main grip
- Mechanical safety clutch
- Electronic overload protection
- Electronic restart interlock
- Separate lubrication chambers for gearing and hammering mechanism
- LED service and status indicators
- Optional TPS theft protection system