HILTI TE7 Hammer Drill

The Hilti TE7 110V Rotary Hammer Drill is a compact and reliable tool designed for drilling and hammer drilling in concrete and masonry. Its two-mode operation, ergonomic D-grip and SDS Plus chuck make it versatile and comfortable for demanding drilling applications.

SPECIFICATIONS

- Weight according to EPTA Procedure 01/2003 2.9 kg
- Hammer drilling diameter range4 - 24 mm
- Optimum hammer drilling range4 - 12 mm
- Single impact energy1.8 J
- Hammer drilling RPM1050 tours/minute
- Full hammering frequency4980 impacts/minute
- FunctionalityIntegrated Dust Removal System (DRS), Removable chuck, Reverse mode, Depth gauge
- Triaxial vibration value for hammer drilling into concrete (ah,HD)11 m/s^2 1
- A-weighted emission sound pressure level89 dB (A) 2

FEATURES

- Two-mode SDS Plus (TE-C) rotary hammer – for hammer drilling and rotary-only drilling
- Ergonomically designed D-grip for comfortable use over long periods
- Excellent performance-to-weight ratio and compact design
- Virtually dustless drilling when used with the DRS-M dust removal system
- Quick-change TE-C Click chuck for versatility and ease of use